

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup>:</b> <b>C10L 1/18</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 94/17160</b> <b>(43) International Publication Date:</b> 4 August 1994 (04.08.94)
<b>(21) International Application Number:</b> PCT/EP94/00148 <b>(22) International Filing Date:</b> 20 January 1994 (20.01.94)  <b>(30) Priority Data:</b> 9301119.5      21 January 1993 (21.01.93)      GB  <b>(71) Applicant (for all designated States except US):</b> EXXON CHEMICAL PATENTS INC. [US/US]; 1900 East Linden Avenue, Linden, NJ 07036 (US).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> CAPROTTI, Rinaldo [IT/GB]; White Witch House, East Hanney, Oxford- shire OX12 0HQ (GB). BOVINGTON, Charles, Herbert [GB/GB]; Asbourne, Kings Lane, Longcot, Faringdon, Oxfordshire SN7 7SS (GB). MACRAE, Colin, John, Dou- glas [GB/GB]; 8 Queens Road, Chandlers Ford, Eastleigh, Hampshire SO5 1AH (GB).  <b>(74) Agents:</b> MANSELL, Keith, Rodney et al.; Exxon Chemical Limited, Exxon Chemical Technology Centre, P.O. Box 1, Abingdon, Oxfordshire OX13 6BB (GB).		<b>(81) Designated States:</b> AU, BR, CA, FI, JP, KR, NO, RU, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> FUEL COMPOSITION  <b>(57) Abstract</b>  A fuel oil composition comprises a major proportion of a liquid hydrocarbon middle distillate fuel having a sulphur concentration of 0.2 % or less by weight based on the weight of the fuel, and a minor proportion of a wear-reducing additive comprising an ester for increasing the lubricity of the fuel.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

## Fuel Composition

This invention relates to fuel compositions useful, for example, to improve lubricity and reduce wear in diesel engines.

5

The art describes esters as additives for diesel engine fuel. For example, US-A-2,527,889 describes polyhydroxy alcohol esters as primary anti-corrosion additives in diesel engine fuel, and GB-A-1,505,302 describes ester combinations including, for example, glycerol monoesters and glycerol diesters as diesel fuel additives, the combinations being described as leading to advantages including less wear of the fuel-injection equipment, piston rings and cylinder liners.

10

GB-A-1,505,302 is, however, concerned with overcoming the operational disadvantages of corrosion and wear by acidic combustion products, residues in the combustion chamber and in the exhaust system. The document states that these disadvantages are due to incomplete combustion under certain operating conditions. Typical diesel fuels available at the date of the document contained, for example, from 0.5 to 1% by weight of sulphur, as elemental sulphur, based on the weight of the fuel.

20

The sulphur content of diesel fuels has now been or will be lowered in a number of countries for environmental reasons, i.e. to reduce sulphur dioxide emissions. Thus, heating oil and diesel fuel sulphur content are being harmonised by the CEC at a maximum of 0.2% by weight, and, at a second stage, the maximum content in diesel fuel will be 0.05% by weight. Complete conversion to the 0.05% maximum may be required during 1996.

25

The process for preparing low sulphur content fuels, in addition to reducing sulphur content, also reduces the content of other components of the fuel such as polyaromatic components and polar components. Reducing one or more of the sulphur, polyaromatic and polar component content of the fuel creates a new problem in use of the fuel, i.e. the ability of the fuel to lubricate the injection system of the engine is reduced such that, for example, the fuel injection pump of the engine can fail relatively early in the life of an engine, failure being, eg. In high pressure fuel injection systems such as high pressure rotary distributors, in-line pumps and unit injectors and injectors. Such severe failures are due to wear that

35

CONFIRMATION COPY

**THIS PAGE BLANK (USPTO)**